

## Standard Dimensions / Weight

Category	Tolerance on Diameter (mm)			Tolerance on Length (mm)			G.E. Standard Weight (kg)	Nipple Weight (kg)	
	Nominal Diameter	Maximum	Minimum	Nominal Diameter	Maximum	Minimum	U H P	3TPI	4TPI
1 4 T	350	358	352	1,800	1,900	1,700	305	14.3	11.3
				2,400	2,525	2,275	400		
1 6 T	400	409	403	1,800	1,900	1,700	395	20.3	15.6
				2,400	2,525	2,275	553		17.6(L)
1 8 T	450	460	454	1,800	1,900	1,700	505	28.0	18.1
				2,400	2,525	2,275	665	33.2(L)	20.5(L)
2 0 T	500	511	505	1,800	1,900	1,700	617	35.3	27.6
				2,100	2,225	1,975	717		
				2,400	2,525	2,275	822	41.4(L)	33.0(L)
				2,700	2,900	2,550	950		
2 2 T	550	562	556	2,100	2,225	1,975	865	35.3	34.8
				2,400	2,525	2,275	990		41.4(L)
				2,700	2,900	2,550	1,135		
2 4 T	600	613	607	2,100	2,225	1,975	1,035	—	39.8
				2,400	2,525	2,275	1,180		48.3(L)
				2,700	2,900	2,550	1,360		
2 6 T	650	663	659	2,400	2,525	2,275	1,370	—	74.0(L)
				2,700	2,900	2,550	1,570		
2 8 T	700	714	710	2,400	2,525	2,275	1,576	—	81.5(L)
				2,700	2,900	2,550	1,840		
3 0 T	750	765	761	2,700	2,900	2,550	2,050	—	106.0(L)
3 2 T	800	816	810	2,700	2,900	2,550	2,448	—	128.0(L)

- See JIS R 7201 for more details.
- The letter " T " in table stands for a taper threads.
- The letter " L " in table stands for a long threads.
- Please consult us concerning sizes that are not specified in the above table.